



### SAM-RTR4

4-port 10/100 router, firewall protection, includes five 12" patch cords and external DC power adapter

### Features

- True plug and play device (uPnP)
- DHCP Client/Server
- NAT-based firewall provides a high level of security
- Hacker Attack and DHCP logging
- Virtual Servers
- Virtual DMZ hosts
- VPN Pass-through support (IPSec, PPTP, L2TP)
- Stateful Packet Inspection
- Email Alerts
- Parental Control

### Product Description

The SAM-RTR4 is an ideal all-in-one networking solution for home and small business users. This platform independent multi-functional broadband router combines a 4-port 10/100 Mbps dual speed switch with firewall capability. It provides a 10/100 WAN port as well as Network Address Translation (NAT) that keeps your internal network hidden from the rest of the Internet. The SAM-RTR4 fully supports VPN tunneling via L2TP, PPTP, and IPSec pass-through allowing remote users secure access to their corporate infrastructure. It also detects, logs, and reports any potential attacks to your network.

The SAM-RTR4 broadband router also allows the connection of multiple users to the Internet using a single WAN IP address. LAN IP addresses are auto-assigned and easily managed through DHCP server capabilities, and the IP routing supports a range of popular applications. This device is a complete networking solution for PC or Mac users.

### Specifications

Ports	Four RJ-45 10/100 Mbps LAN Ports One 10/100 Mbps WAN port
Internet Sharing Methods	Static IP, Dynamic IP, PPTP, PPPoE, NAT
Protocol	TCP/IP IPSec/PPTP/L2TP pass-through (VPN) DHCP PPP Internet Control Protocol PPP Internet Authentication Protocol Point - to - Point Protocol
Cabling Type	10Base-T: UTP/STP Category 3 or 5 100Base-TX: UTP/STP Category 5 or above
Speed	WAN Port: 10 Mbps/100 Mbps with Auto MDI-MDIX LAN Port: 4-Port 10 Mbps/100 Mbps with Auto MDI-MDIX
LEDS	Power, WAN, Link, Activity
NAT Router - Ethernet Interface	IP, PPPoE
Configuration & Management	Web-based
Maximum Users	NAT: 253 Nodes
Upgrade Method	Web
Power	9V 1A
Dimensions	3.75"H x 6.5"W x 1.75"D
Temperature	Operating 0° to 40°C Storage -40° to 70°C

**24/7 Tech Support - 800-SMC-4YOU (800-762-4968)**

Specifications subject to change without notice. Copyright 2006. Revision: 05/07